



codice controcalassa
rough-in housing code
022



codice colori
colour codes
.15 acciaio inox
stainless steel

6521.DKP.T.15 10 W 5 Led 3000 K 1050 lm
6521.DYP.T.15 10 W 5 Led 4000 K 1145 lm
220-240 V 50/60 HZ
vetro trasparente *clear diffuser*
alimentatore incluso *led driver integral*
orientabile *adjustable* 8°





H (m)	Ø (m)	lux med. 3000 K	lux max. 3000 K	lux med. 4000 K	lux max. 4000 K
5	0.84	272	546	297	595
4	0.67	425	853	464	930
3	0.50	756	1517	824	1654
2	0.34	1700	3412	1854	3721
1	0.17	6802	13649	7417	14884

6521.DKE.T.15 10 W 5 Led 3000 K 1050 lm
6521.DYE.T.15 10 W 5 Led 4000 K 1145 lm
220-240 V 50/60 HZ
vetro trasparente *clear diffuser*
alimentatore incluso *led driver integral*
orientabile *adjustable* 8°





H (m)	Ø (m)	lux med. 3000 K	lux max. 3000 K	lux med. 4000 K	lux max. 4000 K
5	2.18	69	148	75	161
4	1.74	108	231	118	252
3	1.31	192	411	209	449
2	0.87	432	926	471	1009
1	0.44	1728	3702	1884	4037

6521.71F.A.15 13W TC-D G24d-1 900 lm
230 V 50 HZ
vetro acidato *acid etched diffuser*
alimentatore ferromagnetico incluso
conventional ballast integral





H (m)	Ø (m)	lux med.	lux max.
5	5.05	4	11
4	4.04	6	17
3	3.03	11	30
2	2.02	24	68
1	1.01	97	273

6521.74F.A.15 18W TC-D G24d-2 1200 lm
230 V 50 HZ
vetro acidato *acid etched diffuser*
alimentatore ferromagnetico incluso
conventional ballast integral







H (m)	Ø (m)	lux med.	lux max.
5	5.05	5	15
4	4.04	8	23
3	3.03	16	40
2	2.02	32	91
1	1.01	130	364



codice controcalassa
rough-in housing code
024

codice colori
colour codes
.15 acciaio inox
stainless steel



5613.CGA.T.15 26 W 1 Led 3000 K 2689 lm
5613.CHA.T.15 26 W 1 Led 4000 K 2810 lm
220-240 V 50/60 HZ
vetro trasparente *clear diffuser*
alimentatore incluso *led driver integral*



codice controcalassa
rough-in housing code
024



codice colori
colour codes
.15 acciaio inox
stainless steel

5613.E9A.T.15 20 W HIT G8,5 1700 lm
220-240 V 50/60 HZ
vetro trasparente *clear diffuser*
alimentatore elettronico incluso
electronic ballast integral





H (m)	Ø (m)	lux med.	lux max.
5	9.90	3	9
4	7.92	5	14
3	5.94	8	25
2	3.96	20	56
1	1.98	80	226

5613.F6A.T.15 35 W HIT G8,5 3300 lm
230 V 50 HZ
vetro trasparente *clear diffuser*
alimentatore ferromagnetico incluso
conventional ballast integral





H (m)	Ø (m)	lux med.	lux max.
5	9.90	4	18
4	7.92	6	29
3	5.94	10	51
2	3.96	23	116
1	1.98	95	466

5613.59A.T.15 70 W HIT-DE /
HST-DE Rx7s 6500 lm
230 V 50 HZ
vetro trasparente *clear diffuser*
alimentatore ferromagnetico incluso
conventional ballast integral





H (m)	Ø (m)	lux med.	lux max.
5	10.06	21	59
4	8.04	33	92
3	6.08	59	163
2	4.10	132	356
1	2.12	527	1471

5613.95A.T.15 26 W TC-DE G24q-3 1800 lm
230 V 50 HZ
vetro trasparente *clear diffuser*
alimentatore elettronico incluso
electronic ballast integral





H (m)	Ø (m)	lux med.	lux max.
5	1.21	2	8
4	8.97	4	13
3	6.72	6	24
2	4.48	14	52
1	2.24	57	208





codice controscassa
rough-in housing code
024
codice colori
colour codes
.15 acciaio inox
stainless steel

5613.59T.A.15 70 W HIT-DE /
HST-DE Rx7s 6500 lm
230 V 50 HZ
vetro acidato acid etched diffuser
alimentatore ferromagnetico incluso
conventional ballast integral






H (m)	Ø (m)	lux med.	lux max.
5	10.57	9	45
4	8.46	15	70
3	6.34	26	124
2	4.23	58	278
1	2.11	234	1113

5613.96F.A.15 2x26 W TC-DE G24q-3 2x1800 lm
220-240 V 50/60 HZ
vetro acidato acid etched diffuser
alimentatore elettronico incluso
electronic ballast integral





H (m)	Ø (m)	lux med.	lux max.
5	15.40	2	22
4	12.32	3	35
3	9.24	5	62
2	6.16	11	139
1	3.08	45	557





codice controscassa
rough-in housing code
148
codice colori
colour codes
.15 acciaio inox
stainless steel




5615.CDA.T.15 39 W 1 Led 3000 K 3765 lm
5615.CEA.T.15 39 W 1 Led 4000 K 3932 lm
220-240 V 50/60 HZ
vetro trasparente clear diffuser
alimentatore incluso led driver integral



5615.61A.T.15 150 W HIT-DE /
HST-DE Rx7s 13500 lm
230 V 50 HZ
vetro trasparente clear diffuser
alimentatore ferromagnetico incluso
conventional ballast integral





H (m)	Ø (m)	lux med.	lux max.
5	10.06	48	130
4	8.04	72	202
3	6.08	129	358
2	4.10	290	810
1	2.12	1159	3236




codice controscassa
rough-in housing code
148
codice colori
colour codes
.15 acciaio inox
stainless steel

5615.61T.A.15 150 W HIT-DE /
HST-DE Rx7s 13500 lm
230 V 50 HZ
vetro acidato acid etched diffuser
alimentatore ferromagnetico incluso
conventional ballast integral




H (m)	Ø (m)	lux med.	lux max.
5	10.76	21	132
4	8.42	33	206
3	6.34	58	367
2	4.23	131	825
1	2.11	509	3300

Accessori Midicarrera Midicarrera accessories




276
Connettore rapido IP 68
IP 68 fast connector




279
Connettore per cablaggio in cascata IP 68
IP 68 connector for through wiring


Accessori Carrera Carrera accessories



276
Connettore rapido IP 68
IP 68 fast connector



107
Vetro anti-scivolo
fattore R12 DIN 51130
anti-slip glass
factor R12 DIN 51130



279
Connettore per cablaggio in cascata IP 68
IP 68 connector for through wiring

